

KISS 2U V2 PCI 762



HIGH PERFORMANCE COMPUTER PLATFORM FOR CHALLENGING OR NOISE SENSITIVE ENVIRONMENTS

- ▶ low noise < 35 dBa
- ▶ rugged design - shock protected drive bays
- ▶ easy customization with modified standard (MoSt) concept
- ▶ predictable maintenance with remote diagnostic

POSSIBILITIES START HERE



► TECHNICAL INFORMATION

SYSTEM		KISS 2U V2 PCI 762
DIMENSION (H X W X D)		88 x 482 x 472 mm (2U x 19" x 18.58")
WEIGHT		Approx. 8 kg
FRONT I/Os		2x USB 2.0
REAR I/Os		2x GB LAN, 2x USB 3.0, VGA 2x RS232 on extra Slotbracket
FRONT CONTROLS		ATX Switch
ACCESSIBLE DRIVE BAYS		1x 5.25", 1x 3.5"
INTERNAL DRIVE BAYS		1x 3.5"
POWER SUPPLY		AC 400 W 80+, 100-240 V AC 400 W (80+)
EXPANSION SLOTS		3x PCI 32 Bit, 1x PCI-ex 16, 1x PCI-ex 4 or 4x PCI-ex 4, 1x PCI-ex 16
CHIPSET		Q77
CPU BOARD		PCI 762
MEMORY		Upto 16 GB DDR3
PROCESSOR		i3-3220 3.3 GHz i5-3550S 3.0 GHz i7-3770 3.4 GHz
COOLING		Two hot swappable chassis fans, air filter
TEMPERATURE	NON-OPERATING OPERATING	-20°C to +70°C (-4°F - 154°F) 0°C to +50°C (32°F - 122°F)
HUMIDITY	OPERATING/NON OPERATING	10-95 % relative humidity at 40 C° non condensing
SHOCK	OPERATING	15g, 11ms
VIBRATION	OPERATING	10-500 Hz, 1g
NOISE		< 35 dBA
APPROVALS		CE
PROTECTION CLASS		IP 20 optional IP 52
OPTIONS		DVD RW, KISS DA135, KISS DA425, KISS StorSlim, PCCM, Slide rails

► ORDERING INFORMATION

RECOMMENDED CONFIGURATION	DESCRIPTION	MATERIAL NUMBER
KISS 2U V2 PCI762	KISS 2U PCI762, Intel® i7-3770, 16 GB DDR, SATA 1 TB, AC PSU 400 W, 2x PCIe, 3x PCI, 5,25" DVD/RW, Windows 7 Ultimate 64 bit	2-A0JA-2004
KISS 2U V2 PCI762	KISS 2U PCI762, Intel® i5-3550S, 16 GB DDR, SATA 1 TB, AC PSU 400 W, 2x PCIe, 3x PCI, 5,25" DVD/RW, Windows 7 Ultimate 64 bit	2-A0JA-2005
KISS 2U V2 PCI762	KISS 2U PCI762, Intel® i3-3220, 8 GB DDR, SATA 1 TB, AC PSU 400 W, 2x PCIe, 3x PCI, 5,25" DVD/RW, Windows 7 Ultimate 64 bit	2-A0JA-2006
BAREBONE KISS 2U V2 PCI762	KISS 2U PCI762, AC PSU 400 W, 2x PCIe, 3x PCI, CPU Cooler	2-A0JA-0005

► CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: +49 821 4086 0
Fax: +49 821 4086 111
info@kontron.com

NORTH AMERICA

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn