

CP-ASM3, CP-ASM4



READY AVAILABLE 3U/4U CompactPCI® CARD CAGES

- ▶ 19" racks with RIO and FAN options
- ▶ Industrial power supplies from 14 VDC to 260 VAC
- ▶ Backplanes with 2 to 8 slots segments
- ▶ EMI protected and CE compliant

POSSIBILITIES START HERE



CP-ASM3 / CP-ASM4 is a series of ready integrated standard card cages for 3U CompactPCI®, based on the quality and experience of the technology leader.

CompactPCI® is the most accepted modular standard throughout the ICT market segments. CompactPCI® is loved for any application, where openness, modularity, robustness, reliability, or longevity is an advantage. It provides outstanding.

- **Flexibility:** just plug another I/O board where needed
- **Variability:** upgrade to another CPU for higher performance
- **Longevity:** switch over to next generation CPU blade
- **Supplier-independency:** for special needs, select any market available component

► TECHNICAL INFORMATION

DIMENSIONS	84HP RACK 42HP RACK 84HP FAN TRAY 42HP FAN TRAY	483 x 133 x 282 mm / 84HP, 3U, 275 mm 220 x 133 x 242 mm / 42HP, 3U, 235 mm 483 x 45 x 282 mm / 84HP, 1U, 275 mm 220 x 45 x 242 mm / 42HP, 1U, 235 mm
P47-STYLE POWER SUPPLY	200 WATT AC 200 WATT DC 36 - 75 VDC 200 WATT DC 18 - 36 VDC	CP3-SVE-P200AC - Input: 85-264 VAC - Max Output: 5 V/40 A, 3.3 V/40 A, +12 V/5.5 A, -12 V/1.5 A. - Dimension: 3U, 8HP - Cooling: Forced airflow mandatory! - Characteristics: Hot swappable, redundant CP3-SVE-P200DC - Input: 36 - 75 VDC - Max Output: 5 V/40 A, 3.3 V/40 A, +12 V/5.5 A, -12 V/1.5 A. - Dimension: 3U, 8HP - Cooling: Forced airflow mandatory! - Characteristics: Hot swappable, redundant CP3-SVE-P200DC - Input: 18-36 VDC - Max Output: 5 V/25 A, 3.3 V/36 A, +12 V/3 A, -12 V/0.5 A - Dimension: 3U, 8HP - Cooling: Forced airflow mandatory! - Characteristics: Hot swappable, redundant
M-STYLE POWER SUPPLY	180 WATT AC 150 WATT DC 100 WATT DC	CP3-SVE-M180AC - Input: 85-264 VAC - Max Output: 5 V/20 A, 3.3 V/14 A, +12 V/2 A, -12 V/1 A. - Dimension: 3U, 12HP - Cooling: Free convection airflow - Characteristics: Not hot swappable, not redundant CP3-SVE-M150DC - Input: 36-76 VDC - Max Output: 5 V/14 A, 3.3 V/14 A, +12 V/2 A, -12 V/1 A. - Dimension: 3U, 12HP - Cooling: Free convection airflow - Characteristics: Not hot swappable, not redundant CP3-SVE-M100DC - Input: 14,4-154 - Max Output: 5V/10A, 3.3V/12A, +12V/9A - Dimension: 3U, 12HP - Cooling: Free convection airflow - Characteristics: Extended temperature, conformal coating, EN50155

For further information refer to the respective manuals of the power supplies or CompactPCI® backplanes.



// CP-ASM4R-84F-P200AC-B0800-STD

► TECHNICAL INFORMATION

COMPACTPCI® BACKPLANE	<p>FOR P47 STYLE PSU</p> <p>FOR M-STYLE PSU</p>	<p>CP3-BP8-P47-RIO</p> <ul style="list-style-type: none"> - PSU connector: P47 - Slot: 8, all 32 bit with Rear I/O right - System slot: CP3-BP8-M-RIO - PSU connector: M-style - Slot: 8, all 32 bit with Rear I/O right - System slot:
1U FAN TRAY	<p>84HP / 1U-275MM / 3.6W</p> <p>84HP / 1U-275MM / 15W</p> <p>42HP / 1U-235MM / 1.2W</p> <p>42HP / 1U-235MM / 5.6W</p>	<p>CP-MKIT-FAN-84-3</p> <ul style="list-style-type: none"> - Power consumption: 12 VDC / 3x 1.2 Watt - Airflow: 3x 95 m³/h (56cfm) / average of 1.25 m/s (250lfm) CP-MKIT-FAN-84-15 - Power consumption: 12 VDC / 3x 5 Watt - Airflow: 3x 170 m³/h (100cfm) / average of 2.5 m/s (500lfm) CP-MKIT-FAN-42-1 - Power consumption: 12 VDC / 1x 1.2 Watt - Airflow: 1x 95 m³/h (56cfm) / average of 0.8 m/s (160lfm) CP-MKIT-FAN-42-5 - Power consumption: 12 VDC / 4x 1.4 Watt - Airflow: 4x 56 m³/h (33cfm) / average of 1.1 m/s (220lfm)
DISK DRIVE ASSEMBLY KITS	<p>SINGLE 2.5" SATA HDD/SSD</p> <p>DOUBLE 2.5" SATA HDD/SSD</p>	<p>CP-HDD-S-KIT-S</p> <p>CP-HDD-S-KIT-D</p>
GENERAL*	<p>AMBIENT TEMPERATURE</p> <p>HUMIDITY</p> <p>PROTECTION</p> <p>OVER VOLTAGE CATAGORY</p> <p>PROTECTION CLASS</p> <p>EMI</p> <p>SAFETY</p>	<p>0 °C to +50 °C</p> <p>Up to 93 % RH at 40 °C, non-condensing (acc. To IEC 60068-2-78)</p> <p>IP20</p> <p>2</p> <p>1</p> <p>EN55022 / EN55024</p> <p>EN60950-1</p>

* All systems described in the ordering list are conform to or better than.



// CP-ASM3R-84-M100DCWV-B0800-STD

► ORDERING INFORMATION

ARTICLE *	DESCRIPTION
COMPACTPCI® CARD CAGE 84HP	
CP-ASM3R-84-P200AC-B0800-STD CP-ASM4R-84F-P200AC-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt AC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-P200DC48V-B0800-STD CP-ASM4R-84F-P200DC48V-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt 48VDC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-P200DC24V-B0800-STD CP-ASM4R-84F-P200DC24V-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt 24VDC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-M180AC-B0800-STD CP-ASM4R-84F-M180AC-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, M-style 180 Watt AC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-M100DCWV-B0800-STD CP-ASM4R-84F-M100DCWV-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, M-style 100 Watt wide range PSU 16.8-137.5 VDC operating and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3.... CP-ASM4....	Any kind of additional 3U and 4U customized rack assemblies on request.
COMPACTPCI® CARD CAGE 42HP	
CP-ASM3-42-M100DCWV-B0400-STD CP-ASM4-42F-M100DCWV-B0400-STD	3U CompactPCI® rack 42HP, 235mm depth wall-mount, with M-style 100W wide range PSU 16.8-137.5 VDC operating, 4 slot backplane, 4U variant including 1U fantray
CP-ASM4R-44F-M180AC-B0500-STD-TT	4U CompactPCI® table top rack with RIO option and fans, 44HP, M-style 180 Watt AC PSU, 5 slot backplane
DISK DRIVE ASSEMBLY KITS	
CP-HDD-S-KIT-S	SATA HDD/SSD carrier, 1 slot backplane, SATA cable
CP-HDD-S-KIT-D	2x SATA HDD/SSD carrier, 2 slot backplane, 2x SATA cable
CP-MKIT-CDROM	CDROM Assembly Set, 5.25", 32HP Front
CP-DVDRW-SATA	SATA re-writable CD/DVD ROM for CompactPCI®

*Drives and CompactPCI® boards can be integrated on request.

Moreover: dedicated system platforms

Ask for your entire platform solution for 3U CompactPCI®, based on a CP-ASM3 / CP-ASM4 rack variant and the right selection out of Kontron's rich CPU blade portfolio, including periphery which fulfills your I/O, storage and networking requirements. Optionally, you may perform the hardware integration yourself. Or, in order to fully concentrate on your application, you may leave the integration to Kontron, and consequently address the platform responsibility to Kontron, which includes co-operability, obsolescence, environmental and EMC criteria of the system.

Dedicated project management

As a global company, Kontron has knowledgeable teams to support you in your region. Through your local project manager you have worldwide access to immense specialist know-how. Your project manager guides you securely through the entire design-in process to productionready product by means of a precise gate project plan. This allows you to concentrate on your core business and still retain an overview and full control of development, documentation, and production, including unique test processes, systems and procedures.

► CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com

NORTH AMERICA

9477 Waples Street
San Diego, CA 92121
USA
Tel.: + 1 888 294 4558
Fax: + 1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn