

KISS 1U SHORT KTQM77



SCALABLE INDUSTRIAL COMPUTER PLATFORM FOR NOISE SENSITIVE ENVIRONMENTS

- ▶ low noise (~40 dBA)
- ▶ easy customization with modified standard (MoSt) concept
- ▶ low installation height

POSSIBILITIES START HERE



► TECHNICAL INFORMATION

SYSTEM		KISS 1U Short KTQM77
DIMENSION (H X W X D)		44 x 482 x 350 mm (1U x 19" x 13.78")
WEIGHT		Approx. 7 kg
FRONT I/Os		4x USB
REAR I/Os		6x USB 2.0, 3x GByte LAN 2x Display port, 1 DVI-I Audio
FRONT CONTROLS		Power button
EXTERNALLY ACCESSIBLE DRIVE BAYS		1x 3.5", 1 SLIM Bay
INTERNAL DRIVE BAYS		1x 2.5"
POWER SUPPLY		100-240 V AC, 270 W wide Range
EXPANSION SLOT		1x PCI_e x16
MEMORY		Up to 16 GByte DDR3
PROCESSOR		i3-3120ME, i5-3610ME, i7-3610QE
TEMPERATURE	NON OPERATING OPERATING	-20 °C to + 70 °C 0 °C to + 45 °C
HUMIDITY	NON OPERATING OPERATING	10-90 % 20-90 %
SHOCK	NON OPERATING OPERATING	30 g 11 ms 15 g 30 ms vertical, 10 g 45 ms horizontal
VIBRATION		1 g 10-500 Hz
NOISE		~ 40 dBA
APPROVALS		CE, designed to meet UL, CB Scheme
MTBF		30.000 h at 25 °C (77 °F)
PROTECTION CLASS		Front IP20
OPTIONS		KISS Stor Slim, DVD R/W

► CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com

NORTH AMERICA

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: + 1 888 294 4558
Fax: + 1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn